
Inhaltsverzeichnis

DXL - APRSmap englisch

Versionsgeschichte interaktiv durchsuchen
VisuellWikitext

Version vom 8. September 2014, 22:17
Uhr (Quelltext anzeigen)
OE2WAO (Diskussion | Beiträge)
K
← Zum vorherigen Versionsunterschied

Version vom 8. September 2014, 22:23
Uhr (Quelltext anzeigen)
OE2WAO (Diskussion | Beiträge)
Zum nächsten Versionsunterschied →

Zeile 8:

A lot of documentation work has to be done soon !!

Zeile 8:

A lot of documentation work has to be done soon !!

+

==Features==

+

* OpenSource and already compiled for windows and linux

+

* 100%iqe compliance with the current APRS protocol specifications

+

* No installation required, just copy and start

+

* No unnecessary menus, focus is on the representation

+

* IP-based, out-of-the-box network-ready in HAMNET and Internet

+

* Operation via shortcuts

+

* Local serial connection (TNC) possible - operating as an RF IGATE

+

* Several MapSources can be used. By default, this is OSM - OpenStreetMap

+

* Track filter for delayed / late / repeated packets "F"

+

* Radio propagation calculation (since v0.36) "R"

+

* Animation of tracks with timeline "A"

+

* Animation of the temperature distribution "W"

	+	* Messaging
==Software==		==Software==

Version vom 8. September 2014, 22:23 Uhr



Für die deutsche Version dieses Projekts [>>hier klicken<<](#)

APRSmap is a new APRS client software by OE5DXL, which is based on the [OSM](#) map source. It allows a lot of features in only one program by a good usability. NO installation is required, just put it on a disk and start it!

Datei: [aprsmap.png](#)

A lot of documentation work has to be done soon !!

Features

- OpenSource and already compiled for windows and linux
- 100%ige compliance with the current APRS protocol specifications
- No installation required, just copy and start
- No unnecessary menus, focus is on the representation
- IP-based, out-of-the-box network-ready in HAMNET and Internet
- Operation via shortcuts
- Local serial connection (TNC) possible - operating as an RF IGATE
- Several MapSources can be used. By default, this is OSM - OpenStreetMap
- Track filter for delayed / late / repeated packets "F"
- Radio propagation calculation (since v0.36) "R"
- Animation of tracks with timeline "A"
- Animation of the temperature distribution "W"
- Messaging

Software

The software is available for OS like WINDOWS, LINUX and systems based on ARM structures like raspberry pi.

Windows version

- [download via Wiki](#) (Datei: [Aprsmap-all.zip](#))
- [download via HAMNET](#) with latest updates (*HAMNET-connection required*)