

Datei:Dcma82.pdf

Basisinformationen

Anzeigetitel	Datei:Dcma82.pdf																				
Standardsortierschlüssel	Dcma82.pdf																				
Seitenlänge (in Bytes)	0																				
Namensraum	Datei																				
Seitenkennnummer	550																				
Seiteninhaltssprache	de-formal - Deutsch (Sie-Form)																				
Seiteninhaltsmodell	Wikitext																				
Indizierung durch Suchmaschinen	Erlaubt																				
Anzahl der Weiterleitungen zu dieser Seite	0																				
Prüfsummenwert	165afc6688c98de6df6ab051604abfe0d2d228d3																				
Seitenbild	<div style="border: 1px solid black; padding: 5px;"> <p style="text-align: center; margin: 0;">Mini-PCI WiFi Module : DCMA-82 Industrial grade high power 802.11a/b/g 108Mbps wifi mini-PCI module, RoHS compliance</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="background-color: #f2f2f2;">Specifications</th> <th style="background-color: #f2f2f2;">Mini-PCI WiFi Module : DCMA-82</th> </tr> </thead> <tbody> <tr> <td>Standard conformance</td> <td>IEEE 802.11a, 802.11b, 802.11g</td> </tr> <tr> <td>Frequency Range</td> <td> <ul style="list-style-type: none"> • A mode: <ul style="list-style-type: none"> 5.15 ~ 5.35GHz & 5.725 ~ 5.825GHz for US 4.9 ~ 5.25GHz for Japan 5.15 ~ 5.35GHz & 5.47 ~ 5.725GHz for ETSI • B/G mode: <ul style="list-style-type: none"> 2.400 ~ 2.4835GHz for US, Canada, ETSI and Japan 2.471 ~ 2.497GHz for Japan </td> </tr> <tr> <td>Interface</td> <td>32-bit mini-PCI Type IIIA</td> </tr> <tr> <td>Operation Voltage</td> <td>3.3VDC (eVDC optional by project)</td> </tr> <tr> <td>Modulation Technique</td> <td> <ul style="list-style-type: none"> • 802.11a: <ul style="list-style-type: none"> OFDM with BPSK, QPSK, OAM, and 64QAM • 802.11b: <ul style="list-style-type: none"> DSSS with CCK, DQPSK, DBPSK • 802.11g: <ul style="list-style-type: none"> OFDM with BPSK, QPSK, OAM and 64QAM DSSS with CCK, DQPSK, DBPSK </td> </tr> <tr> <td>Data Rate</td> <td> <ul style="list-style-type: none"> • 802.11a (Normal mode): 54, 48, 36, 24, 18, 12, 9, 6Mbps, auto-fallback • 802.11a (Turbo mode): 108, 96, 72, 48, 36, 24, 18, 12 Mbps, auto-fallback • 802.11b/g: 11, 5.5, 2, 1 Mbps, auto-fallback, up to 54 Mbps • 802.11g (Super mode): up to 108 Mbps </td> </tr> <tr> <td>Operating Range (subject to the environment and antenna)</td> <td> <ul style="list-style-type: none"> • 802.11a <ul style="list-style-type: none"> Outdoor: over 350meter@6Mbps Indoor: 35 ~ 100meter@6Mbps • 802.11b <ul style="list-style-type: none"> Outdoor: over 350meter@11Mbps Indoor: 35 ~ 100meter@11Mbps • 802.11g <ul style="list-style-type: none"> Outdoor: over 350meter@6Mbps Indoor: 35 ~ 100meter@6Mbps </td> </tr> <tr> <td>Operating Channels</td> <td> <ul style="list-style-type: none"> • 802.11a <ul style="list-style-type: none"> US/Canada: 12 non-overlapping channels (5.15 ~ 5.35GHz, 5.725 ~ 5.825GHz) Europe: 19 non-overlapping channels (5.15 ~ 5.35GHz, 5.47 ~ 5.725GHz) Japan: 4 non-overlapping channels (5.15 ~ 5.25GHz) • 802.11b/g <ul style="list-style-type: none"> US/Canada: 11 (1 ~ 11) Major European country: 13 (1 ~ 13) France: 4 (10 ~ 13) Japan: 14 for 11b (1 ~ 13 or 14th), 13 for 11g (1 ~ 13) </td> </tr> <tr> <td>Power Consumption</td> <td> <ul style="list-style-type: none"> • 3.3V DC: <ul style="list-style-type: none"> 802.11a mode: 850mA (min.), 950mA(typical), 1050mA(max.) 802.11g mode: 700mA (min.), 800mA(typical), 900mA(max.) 802.11b mode: 700mA (min.), 800mA(typical), 900mA(max.) </td> </tr> </tbody> </table> </div>	Specifications	Mini-PCI WiFi Module : DCMA-82	Standard conformance	IEEE 802.11a, 802.11b, 802.11g	Frequency Range	<ul style="list-style-type: none"> • A mode: <ul style="list-style-type: none"> 5.15 ~ 5.35GHz & 5.725 ~ 5.825GHz for US 4.9 ~ 5.25GHz for Japan 5.15 ~ 5.35GHz & 5.47 ~ 5.725GHz for ETSI • B/G mode: <ul style="list-style-type: none"> 2.400 ~ 2.4835GHz for US, Canada, ETSI and Japan 2.471 ~ 2.497GHz for Japan 	Interface	32-bit mini-PCI Type IIIA	Operation Voltage	3.3VDC (eVDC optional by project)	Modulation Technique	<ul style="list-style-type: none"> • 802.11a: <ul style="list-style-type: none"> OFDM with BPSK, QPSK, OAM, and 64QAM • 802.11b: <ul style="list-style-type: none"> DSSS with CCK, DQPSK, DBPSK • 802.11g: <ul style="list-style-type: none"> OFDM with BPSK, QPSK, OAM and 64QAM DSSS with CCK, DQPSK, DBPSK 	Data Rate	<ul style="list-style-type: none"> • 802.11a (Normal mode): 54, 48, 36, 24, 18, 12, 9, 6Mbps, auto-fallback • 802.11a (Turbo mode): 108, 96, 72, 48, 36, 24, 18, 12 Mbps, auto-fallback • 802.11b/g: 11, 5.5, 2, 1 Mbps, auto-fallback, up to 54 Mbps • 802.11g (Super mode): up to 108 Mbps 	Operating Range (subject to the environment and antenna)	<ul style="list-style-type: none"> • 802.11a <ul style="list-style-type: none"> Outdoor: over 350meter@6Mbps Indoor: 35 ~ 100meter@6Mbps • 802.11b <ul style="list-style-type: none"> Outdoor: over 350meter@11Mbps Indoor: 35 ~ 100meter@11Mbps • 802.11g <ul style="list-style-type: none"> Outdoor: over 350meter@6Mbps Indoor: 35 ~ 100meter@6Mbps 	Operating Channels	<ul style="list-style-type: none"> • 802.11a <ul style="list-style-type: none"> US/Canada: 12 non-overlapping channels (5.15 ~ 5.35GHz, 5.725 ~ 5.825GHz) Europe: 19 non-overlapping channels (5.15 ~ 5.35GHz, 5.47 ~ 5.725GHz) Japan: 4 non-overlapping channels (5.15 ~ 5.25GHz) • 802.11b/g <ul style="list-style-type: none"> US/Canada: 11 (1 ~ 11) Major European country: 13 (1 ~ 13) France: 4 (10 ~ 13) Japan: 14 for 11b (1 ~ 13 or 14th), 13 for 11g (1 ~ 13) 	Power Consumption	<ul style="list-style-type: none"> • 3.3V DC: <ul style="list-style-type: none"> 802.11a mode: 850mA (min.), 950mA(typical), 1050mA(max.) 802.11g mode: 700mA (min.), 800mA(typical), 900mA(max.) 802.11b mode: 700mA (min.), 800mA(typical), 900mA(max.)
Specifications	Mini-PCI WiFi Module : DCMA-82																				
Standard conformance	IEEE 802.11a, 802.11b, 802.11g																				
Frequency Range	<ul style="list-style-type: none"> • A mode: <ul style="list-style-type: none"> 5.15 ~ 5.35GHz & 5.725 ~ 5.825GHz for US 4.9 ~ 5.25GHz for Japan 5.15 ~ 5.35GHz & 5.47 ~ 5.725GHz for ETSI • B/G mode: <ul style="list-style-type: none"> 2.400 ~ 2.4835GHz for US, Canada, ETSI and Japan 2.471 ~ 2.497GHz for Japan 																				
Interface	32-bit mini-PCI Type IIIA																				
Operation Voltage	3.3VDC (eVDC optional by project)																				
Modulation Technique	<ul style="list-style-type: none"> • 802.11a: <ul style="list-style-type: none"> OFDM with BPSK, QPSK, OAM, and 64QAM • 802.11b: <ul style="list-style-type: none"> DSSS with CCK, DQPSK, DBPSK • 802.11g: <ul style="list-style-type: none"> OFDM with BPSK, QPSK, OAM and 64QAM DSSS with CCK, DQPSK, DBPSK 																				
Data Rate	<ul style="list-style-type: none"> • 802.11a (Normal mode): 54, 48, 36, 24, 18, 12, 9, 6Mbps, auto-fallback • 802.11a (Turbo mode): 108, 96, 72, 48, 36, 24, 18, 12 Mbps, auto-fallback • 802.11b/g: 11, 5.5, 2, 1 Mbps, auto-fallback, up to 54 Mbps • 802.11g (Super mode): up to 108 Mbps 																				
Operating Range (subject to the environment and antenna)	<ul style="list-style-type: none"> • 802.11a <ul style="list-style-type: none"> Outdoor: over 350meter@6Mbps Indoor: 35 ~ 100meter@6Mbps • 802.11b <ul style="list-style-type: none"> Outdoor: over 350meter@11Mbps Indoor: 35 ~ 100meter@11Mbps • 802.11g <ul style="list-style-type: none"> Outdoor: over 350meter@6Mbps Indoor: 35 ~ 100meter@6Mbps 																				
Operating Channels	<ul style="list-style-type: none"> • 802.11a <ul style="list-style-type: none"> US/Canada: 12 non-overlapping channels (5.15 ~ 5.35GHz, 5.725 ~ 5.825GHz) Europe: 19 non-overlapping channels (5.15 ~ 5.35GHz, 5.47 ~ 5.725GHz) Japan: 4 non-overlapping channels (5.15 ~ 5.25GHz) • 802.11b/g <ul style="list-style-type: none"> US/Canada: 11 (1 ~ 11) Major European country: 13 (1 ~ 13) France: 4 (10 ~ 13) Japan: 14 for 11b (1 ~ 13 or 14th), 13 for 11g (1 ~ 13) 																				
Power Consumption	<ul style="list-style-type: none"> • 3.3V DC: <ul style="list-style-type: none"> 802.11a mode: 850mA (min.), 950mA(typical), 1050mA(max.) 802.11g mode: 700mA (min.), 800mA(typical), 900mA(max.) 802.11b mode: 700mA (min.), 800mA(typical), 900mA(max.) 																				

1/3

Seitenschutz

Bearbeiten	Alle Benutzer (unbeschränkt)
Verschieben	Alle Benutzer (unbeschränkt)
Hochladen	Alle Benutzer (unbeschränkt)

[Das Seitenschutz-Logbuch für diese Seite ansehen.](#)

Versionsgeschichte

Seitenersteller	OE2WAO (Diskussion Beiträge)
Datum der Seitenerstellung	14:39, 16. Jan. 2009
Letzter Bearbeiter	OE2WAO (Diskussion Beiträge)
Datum der letzten Bearbeitung	14:39, 16. Jan. 2009
Gesamtzahl der Bearbeitungen	1
Gesamtzahl unterschiedlicher Autoren	1
Anzahl der kürzlich erfolgten Bearbeitungen (in den letzten 90 Tagen)	0
Anzahl unterschiedlicher Autoren der kürzlich erfolgten Bearbeitungen	0