

## Inhaltsverzeichnis

1. Datei:FT-202-Ad-Slick-Back.jpg .....	2
2. Benutzer Diskussion:OE1CWJ .....	4
3. Benutzer:OE1CWJ .....	5
4. Geschichte UKW Funk .....	6

Datei:FT-202-Ad-Slick-Back.jpg

- Datei
- Dateiversionen
- Dateiverwendung
- Metadaten

**YAESU FT-202R** 2 METER HAND-HELD FM TRANSCEIVER "THE HANDIE"

Handy BNC connector for antenna

S-meter/battery indicator

OFF/ON/Volume control

ANT

C B A

D E F

6 channel capability (3 supplied, 3 optional)

Squelch control

External speaker-microphone jack (option)

VOL

SQL

MIC

**YAESU engineering brings you these top quality features:**

- 1 watt output minimum.
- 6 channel capability (3 supplied, 3 optional).
- Flexible helical whip antenna.
- Equipped with tone burst or subaudible tone squelch.
- Compact size and light weight (less than 1 pound w/o batteries).
- S-meter and battery condition indicator.
- Operates on NiCd or dry cell batteries (not supplied).
- Crisp, clear audio on transmit and receive.
- Built-in speaker and condenser microphone.
- Optional remote speaker-microphone.
- Impact-resistant ABS plastic body.
- Convenient carrying case.

**A top performance package you can hold in your hand. . .yours today from YAESU.**

■ **SPECIFICATIONS**

**GENERAL**  
 Frequency coverage: 144-146 MHz or 144 - 148 MHz.  
 Number of channels: 6 (3 provided, 3 optional).  
 Emission type: F3  
 Batteries (not supplied): AA size, NiCd (8 needed) or dry cells (7 needed).  
 Voltage requirement: 9.6 VDC ±10%, maximum 12 VDC.  
 Current consumption: RX 200 mA (30 mA squelched) TX 500 mA

Case dimensions: 67 x 49 x 171 mm,  
 Weight (less batteries): 400 g.

**TRANSMITTER**  
 Power output: 1 watt.  
 Deviation: ±5 kHz.  
 Spurious radiation: 60 dB down or better.  
 Microphone: Condenser type, 2000 ohm impedance.

**RECEIVER**  
 Circuit type: Double conversion superheterodyne.  
 Intermediate frequencies: 1st IF = 10.7 MHz 2nd IF = 455 kHz  
 Sensitivity: 0.32µV for 20 dB quieting.  
 Selectivity: ±20 kHz at 60 dB down.  
 Audio output: 500 mW @ 10% THD.

**YAESU MUSEN CO., LTD.**  
 C. P. O. BOX 1500  
 TOKYO, JAPAN  
 Fox Tango International Http://www.foxtango.org

**YAESU MUSEN U. S. A., INC.**  
 P. O. BOX 498  
 PARAMOUNT, CALIFORNIA 90723, U. S. A.  
 Printed in Japan

Größe dieser Vorschau: 422 x 599 Pixel. Weitere Auflösungen: 169 x 240 Pixel | 1.416 x 2.009 Pixel.

Originaldatei (1.416 x 2.009 Pixel, Dateigröße: 439 KB, MIME-Typ: image/jpeg)

Dateiversionen

Klicken Sie auf einen Zeitpunkt, um diese Version zu laden.

	Version vom	Vorschaubild	Maße	Benutzer	Kommentar
aktuell	13:16, 17. Jul. 2012		1.416 × 2.009 (439 KB)	(Diskussion	Beiträge)

Sie können diese Datei nicht überschreiben.

## Dateiverwendung

Die folgende Seite verwendet diese Datei:

- [Geschichte UKW Funk](#)

## Metadaten

Diese Datei enthält weitere Informationen, die in der Regel von der Digitalkamera oder dem verwendeten Scanner stammen. Durch nachträgliche Bearbeitung der Originaldatei können einige Details verändert worden sein.

<b>Hersteller</b>	HP
<b>Modell</b>	HP psc1600
<b>Erfassungszeitpunkt</b>	23:09, 29. Aug. 2006
<b>Horizontale Auflösung</b>	200 dpi
<b>Vertikale Auflösung</b>	200 dpi
<b>Y und C Positionierung</b>	Benachbart
<b>Sättigung</b>	Normal
<b>Schärfe</b>	Normal
<b>Exif-Version</b>	2.2
<b>Farbraum</b>	sRGB

**Datei:FT-202-Ad-Slick-Back.jpg**

**Datei:FT-202-Ad-Slick-Back.jpg**

**Datei:FT-202-Ad-Slick-Back.jpg**