
Inhaltsverzeichnis

Datei:Grandstream2020-1.PNG

Basisinformationen

Anzeigetitel	Datei:Grandstream2020-1.PNG										
Standardsortierschlüssel	Grandstream2020-1.PNG										
Seitenlänge (in Bytes)	20										
Namensraum	Datei										
Seitenkennnummer	2147										
Seiteninhaltssprache	de-formal - Deutsch (Sie-Form)										
Seiteninhaltsmodell	Wikitext										
Indizierung durch Suchmaschinen	Erlaubt										
Anzahl der Weiterleitungen zu dieser Seite	0										
Prüfsummenwert	020a0186d2bf7615f38a48517ea07829fc24e30a										
Seitenbild	Grandstream Device Configuration <table><tr><th>STATUS</th><th>BASIC SETTINGS</th><th>ADVANCED SETTINGS</th><th>EXT.1</th><th>EXT.2</th></tr><tr><th>ACCOUNT 1</th><th>ACCOUNT 2</th><th>ACCOUNT 3</th><th>ACCOUNT 4</th><th>ACCOUNT 6</th></tr></table> Account Active: ☐ No ☒ Yes Account Name: Hamnet (e.g., MyCompany) SIP Server: voip.oe2xtr.ampr.at (e.g., sip.mycompany.com, or IP address) Outbound Proxy: (e.g., proxy.myprovider.com, or IP address) SIP User ID: <Ham Tel.No> (the user part of an SIP address) Authenticate ID: <Ham Tel.No> (can be same or different from SIP UserID) Authenticate Password: (not displayed for security protection) Name: CALL (optional, e.g., John Doe) Use DNS SRV: ☒ No ☐ Yes User ID is phone number: ☐ No ☒ Yes SIP Registration: ☐ No ☒ Yes Unregister On Reboot: ☒ No ☐ Yes Support SIP Instance ID: ☒ No ☐ Yes Register Expiration: 60 (in minutes, default 1 hour, max 45 days) local SIP port: 5060 (default 5060) SIP Registration Failure Retry Wait Time: 20 (in seconds. Between 1-3600, default is 20) SIP T1 Timeout: 1 sec SIP T2 Interval: 4 sec SIP Transport: ☒ UDP ☐ TCP Use RFC3581 Symmetric Routing: ☐ No ☒ Yes NAT Traversal (STUN): ☒ No ☐ No, but send keep-alive ☐ Yes SUBSCRIBE for MWI: ☒ No ☐ Yes SUBSCRIBE for Registration Event: ☒ No ☐ Yes PUBLISH for Presence: ☒ No ☐ Yes Proxy-Require: Voice Mail UserID: (UserID for voice mail system) Send DTMF: ☒ in-audio ☐ via RTP (RFC2833) ☐ via SIP INFO Early Dial: ☐ No ☒ Yes (use "Yes" only if proxy supports 484 response) Dial Plan Prefix: (this prefix string is added to each dialed number) BLF Call-pickup Prefix: ** (this prefix is prepended when answering call with BLF key) Delayed Call Forward Wait Time: 20 (Allowed range 1-120, in seconds.) Enable Call Features: ☐ No ☒ Yes (if yes, call features using star codes will be supported locally) Call Log: ☒ Log All Calls ☐ Log Incoming/Outgoing only (Missed calls NOT recorded) ☐ Disable Call Log	STATUS	BASIC SETTINGS	ADVANCED SETTINGS	EXT.1	EXT.2	ACCOUNT 1	ACCOUNT 2	ACCOUNT 3	ACCOUNT 4	ACCOUNT 6
STATUS	BASIC SETTINGS	ADVANCED SETTINGS	EXT.1	EXT.2							
ACCOUNT 1	ACCOUNT 2	ACCOUNT 3	ACCOUNT 4	ACCOUNT 6							

Seitenschutz

Bearbeiten	Alle Benutzer (unbeschränkt)
Verschieben	Alle Benutzer (unbeschränkt)
Hochladen	Alle Benutzer (unbeschränkt)

[Das Seitenschutz-Logbuch für diese Seite ansehen.](#)

Versionsgeschichte

Seitenersteller	OE2WNL (Diskussion Beiträge)
Datum der Seitenerstellung	00:56, 16. Mär. 2014
Letzter Bearbeiter	OE2WNL (Diskussion Beiträge)
Datum der letzten Bearbeitung	00:56, 16. Mär. 2014
Gesamtzahl der Bearbeitungen	1
Gesamtzahl unterschiedlicher Autoren	1
Anzahl der kürzlich erfolgten Bearbeitungen (in den letzten 90 Tagen)	0
Anzahl unterschiedlicher Autoren der kürzlich erfolgten Bearbeitungen	0