

Datei:Mercury 8.pdf

Basisinformationen

| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|---|-----------------------------|-----------------------------|--------------------------|------------------------------------|--------|----------------------------------|---------|------------------|----------------------|-----------|---------------------|--|--------------------------|--------------|-----------------|---|------------------------|---------------------------|-------------------|---------------------------------------|---------------------|---------|-----------------------|--|-------------|-------------|--------------------|-------|---------------------|---|--------------------------------|---|
| Anzeigetitel | Datei:Mercury 8.pdf | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Standardsortierschlüssel | Mercury 8.pdf | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Seitenlänge (in Bytes) | 226 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Namensraum | Datei | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Seitenkennnummer | 1035 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Seiteninhaltssprache | de-formal - Deutsch (Sie-Form) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Seiteninhaltsmodell | Wikitext | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Indizierung durch Suchmaschinen | Erlaubt | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Anzahl der Weiterleitungen zu dieser Seite | 0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Prüfsummenwert | 67511f283d0a2d480870ceddee887f8c5532b172 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Seitenbild | <p>Mercury 8 Alphanumeric Pager</p> <p>FEATURES</p> <ul style="list-style-type: none"> 8 Line Alphanumeric Display 21 Characters per Line Zooms to 4 Lines With 17 Characters per Line 8 Digit Code Addresses Button Activated Display Lighting Message Capacity of 60 Messages Up to 500 Characters per Message Practical Alarm Feature Time and Date Stamp Added on Message Receipt Automatic Detection and Rejection of Duplicate Messages 11 Selectable Languages 4 Selectable Alert Tones Windows PC Software Programmable or Exclusive Features Via Pager Buttons 700 Hours of Battery Life on a Single AAA Alkaline <p>SPECIFICATIONS</p> <table border="1"> <tr> <td>Dimensions (Without Holder)</td> <td>75 (L) x 51 (W) x 18 (H) mm</td> </tr> <tr> <td>Dimensions (With Holder)</td> <td>2.9 (L) x 2.0 (W) x 0.7 (H) inches</td> </tr> <tr> <td>Weight</td> <td>0.5g / 0.3oz (including battery)</td> </tr> <tr> <td>Battery</td> <td>1 x AAA alkaline</td> </tr> <tr> <td>Approx. Battery Life</td> <td>700 hours</td> </tr> <tr> <td>Frequencies Covered</td> <td>135-175 MHz 278-287 MHz 406-476 MHz 815-832 MHz</td> </tr> <tr> <td>Signal Transmission Type</td> <td>POCSAG (CDR)</td> </tr> <tr> <td>Channel Spacing</td> <td>VHF: 9kHz / 2.5kHz / 6.25kHz UHF: 4kHz / 5kHz / 12.5kHz 300MHz: 10kHz / 12.5kHz</td> </tr> <tr> <td>Data Transmission Rate</td> <td>51bps, 1200bps or 8400bps</td> </tr> <tr> <td>Modulation System</td> <td>Carrier Frequency Shift Keying (RFSS)</td> </tr> <tr> <td>Frequency Deviation</td> <td>±4.5kHz</td> </tr> <tr> <td>Receiving Sensitivity</td> <td>512 μps SVA/m, 1200bps 7μV/m, 8400bps 8μV/m</td> </tr> <tr> <td>Selectivity</td> <td>65db ±25kHz</td> </tr> <tr> <td>Spurious Rejection</td> <td>60dB+</td> </tr> <tr> <td>Frequency Stability</td> <td>10ppm (LAF) 5ppm (LHF) 3ppm (330 MHz)</td> </tr> <tr> <td>Storage Temperature / Humidity</td> <td>0°C/30% to 50°C/100% at 95% humidity (noncondensing)</td> </tr> </table> <p>Deutschland / Germany HMK GmbH Distribution Obere Zeil 4 61440 Oberursel</p> <p>HMK COMMTECH WIRELESS Commtech Wireless</p> | Dimensions (Without Holder) | 75 (L) x 51 (W) x 18 (H) mm | Dimensions (With Holder) | 2.9 (L) x 2.0 (W) x 0.7 (H) inches | Weight | 0.5g / 0.3oz (including battery) | Battery | 1 x AAA alkaline | Approx. Battery Life | 700 hours | Frequencies Covered | 135-175 MHz 278-287 MHz 406-476 MHz 815-832 MHz | Signal Transmission Type | POCSAG (CDR) | Channel Spacing | VHF: 9kHz / 2.5kHz / 6.25kHz UHF: 4kHz / 5kHz / 12.5kHz 300MHz: 10kHz / 12.5kHz | Data Transmission Rate | 51bps, 1200bps or 8400bps | Modulation System | Carrier Frequency Shift Keying (RFSS) | Frequency Deviation | ±4.5kHz | Receiving Sensitivity | 512 μps SVA/m, 1200bps 7μV/m, 8400bps 8μV/m | Selectivity | 65db ±25kHz | Spurious Rejection | 60dB+ | Frequency Stability | 10ppm (LAF) 5ppm (LHF) 3ppm (330 MHz) | Storage Temperature / Humidity | 0°C/30% to 50°C/100% at 95% humidity (noncondensing) |
| Dimensions (Without Holder) | 75 (L) x 51 (W) x 18 (H) mm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Dimensions (With Holder) | 2.9 (L) x 2.0 (W) x 0.7 (H) inches | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Weight | 0.5g / 0.3oz (including battery) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Battery | 1 x AAA alkaline | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Approx. Battery Life | 700 hours | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Frequencies Covered | 135-175 MHz 278-287 MHz 406-476 MHz 815-832 MHz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Signal Transmission Type | POCSAG (CDR) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Channel Spacing | VHF: 9kHz / 2.5kHz / 6.25kHz UHF: 4kHz / 5kHz / 12.5kHz 300MHz: 10kHz / 12.5kHz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Data Transmission Rate | 51bps, 1200bps or 8400bps | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Modulation System | Carrier Frequency Shift Keying (RFSS) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Frequency Deviation | ±4.5kHz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Receiving Sensitivity | 512 μps SVA/m, 1200bps 7μV/m, 8400bps 8μV/m | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Selectivity | 65db ±25kHz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Spurious Rejection | 60dB+ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Frequency Stability | 10ppm (LAF) 5ppm (LHF) 3ppm (330 MHz) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Storage Temperature / Humidity | 0°C/30% to 50°C/100% at 95% humidity (noncondensing) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Seitenschutz

| | |
|-------------|------------------------------|
| Bearbeiten | Alle Benutzer (unbeschränkt) |
| Verschieben | Alle Benutzer (unbeschränkt) |
| Hochladen | Alle Benutzer (unbeschränkt) |

[Das Seitenschutz-Logbuch für diese Seite ansehen.](#)

Versionsgeschichte

| | |
|---|--|
| Seitenersteller | OE1CMW (Diskussion Beiträge) |
| Datum der Seitenerstellung | 12:10, 2. Mär. 2010 |
| Letzter Bearbeiter | OE1CMW (Diskussion Beiträge) |
| Datum der letzten Bearbeitung | 12:10, 2. Mär. 2010 |
| Gesamtzahl der Bearbeitungen | 1 |
| Gesamtzahl unterschiedlicher Autoren | 1 |
| Anzahl der kürzlich erfolgten Bearbeitungen (in den letzten 90 Tagen) | 0 |
| Anzahl unterschiedlicher Autoren der kürzlich erfolgten Bearbeitungen | 0 |