

Inhaltsverzeichnis

1. MEPT - a WSPR beacon	8
2. Benutzer:Oe1mcu	5

MEPT - a WSPR beacon

Versionsgeschichte interaktiv durchsuchen
VisuellWikitext

Version vom 1. Juli 2009, 09:29 Uhr (Quelltext anzeigen)

Oe1mcu (Diskussion | Beiträge)

(→Connectors:)

← Zum vorherigen Versionsunterschied

Version vom 1. Juli 2009, 09:30 Uhr (Quelltext anzeigen)

Oe1mcu (Diskussion | Beiträge)

(→Features:)

Zum nächsten Versionsunterschied →

Zeile 21: * ""ICSP"" for in circuit serial programming of the PIC processor - == Features: == * Configuration software for Windows	Zeile 21: * ""ICSP"" for in circuit serial programming of the PIC processor + == Ausstattung: == * Configuration software for Windows
Zeile 31: * Multiple DDS & PA modules attachable to one controller * DDS & PA module for 1.8-50MHz with up to 15W -	Zeile 31: * Multiple DDS & PA modules attachable to one controller * DDS & PA module for 1.8-50MHz with up to 15W + * BAnds (80m / 40m / 30m / 20m/ 17m / 15m / 12m / 10m / 6m)

Version vom 1. Juli 2009, 09:30 Uhr

VERSATILE WSPR BEACON for MOBILE and FIXED applications

MEPT = Manned Experimental Propagation Transmitter



Es dauerte einige Monate - aber jetzt ist es (fast) fertig.

A versatile beacon concept that consists of a number modules that can be combined according to the application.

Anschlüsse:

- **USB interface** für die Windows Konfigurations Software
- **serial interface** zum Anschluss der GPS Maus
- **SPI bus** to interconnect the modules
- **ICSP** for in circuit serial programming of the PIC processor

Ausstattung\:

- Configuration software for Windows
- Beacon runs independent from PC
- Time and Location can be derived from GPS signal

-
- Autonomous generation of WSPR data string in local microcontroller
 - Up to 8 different filters selectable through filter switch box
 - Up to 4 Attenuator networks selectable through attenuator switch box
 - Multiple DDS & PA modules attachable to one controller
 - DDS & PA module for 1.8-50MHz with up to 15W
 - BAnds (80m / 40m / 30m / 20m/ 17m / 15m / 12m / 10m / 6m)

At the moment there are two modules. The CPU box with a DDS/PA module and a switch box that can hold up to 8 filter and one attenuator modules



Here you can find an overview of the possible configurations

MEPT CONFIGURATIONS

A detailed description of the individual modules can be found here

MEPT CPU

MEPT switch module

I have a long list of improvements and additions I want to create to my beacon system. Here is a list of my plans (Although I don't know yet where to find the time to do all that)

MEPT_Development_Plan

Weiter Informationen: <http://www.oel1fm.at/>

MEPT - a WSPR beacon: Unterschied zwischen den Versionen

[Versionsgeschichte interaktiv durchsuchen](#)

[Visuell Wikitext](#)

Version vom 1. Juli 2009, 09:29 Uhr (Quelle anzeigen)

[Oe1mcu](#) ([Diskussion](#) | [Beiträge](#))

(→Connectors:)

[← Zum vorherigen Versionsunterschied](#)

Version vom 1. Juli 2009, 09:30 Uhr (Quelle anzeigen)

[Oe1mcu](#) ([Diskussion](#) | [Beiträge](#))

(→Features:)

[Zum nächsten Versionsunterschied →](#)

Zeile 21:

* ""ICSP"" for in circuit serial programming of the PIC processor

– **== Features: ==**

* Configuration software for Windows

Zeile 21:

* ""ICSP"" for in circuit serial programming of the PIC processor

+ **== Ausstattung: ==**

* Configuration software for Windows

Zeile 31:

* Multiple DDS & PA modules attachable to one controller

* DDS & PA module for 1.8-50MHz with up to 15W

–

Zeile 31:

* Multiple DDS & PA modules attachable to one controller

* DDS & PA module for 1.8-50MHz with up to 15W

+ *** BAnds (80m / 40m / 30m / 20m/ 17m / 15m / 12m / 10m / 6m)**

Version vom 1. Juli 2009, 09:30 Uhr

VERSATILE WSPR BEACON for MOBILE and FIXED applications

MEPT = Manned Experimental Propagation Transmitter



Es dauerte einige Monate - aber jetzt ist es (fast) fertig.

A versatile beacon concept that consists of a number modules that can be combined according to the application.

Anschlüsse:

- **USB interface** für die Windows Konfigurations Software
- **serial interface** zum Anschluss der GPS Maus
- **SPI bus** to interconnect the modules
- **ICSP** for in circuit serial programming of the PIC processor

Ausstattung\:

- Configuration software for Windows
- Beacon runs independent from PC
- Time and Location can be derived from GPS signal

- Autonomous generation of WSPR data string in local microcontroller
- Up to 8 different filters selectable through filter switch box
- Up to 4 Attenuator networks selectable through attenuator switch box
- Multiple DDS & PA modules attachable to one controller
- DDS & PA module for 1.8-50MHz with up to 15W
- BAnds (80m / 40m / 30m / 20m/ 17m / 15m / 12m / 10m / 6m)

At the moment there are two modules. The CPU box with a DDS/PA module and a switch box that can hold up to 8 filter and one attenuator modules



Here you can find an overview of the possible configurations

MEPT CONFIGURATIONS

A detailed description of the individual modules can be found here

MEPT CPU

MEPT switch module

I have a long list of improvements and additions I want to create to my beacon system. Here is a list of my plans (Although I don't know yet where to find the time to do all that)

MEPT_Development_Plan

Weiter Informationen: <http://www.oel1fm.at/>

MEPT - a WSPR beacon: Unterschied zwischen den Versionen

[Versionsgeschichte interaktiv durchsuchen](#)

[Visuell Wikitext](#)

Version vom 1. Juli 2009, 09:29 Uhr (Quelle anzeigen)

[Oe1mcu](#) ([Diskussion](#) | [Beiträge](#))

(→Connectors:)

[← Zum vorherigen Versionsunterschied](#)

Version vom 1. Juli 2009, 09:30 Uhr (Quelle anzeigen)

[Oe1mcu](#) ([Diskussion](#) | [Beiträge](#))

(→Features:)

[Zum nächsten Versionsunterschied →](#)

Zeile 21:

* ""ICSP"" for in circuit serial programming of the PIC processor

– **== Features: ==**

* Configuration software for Windows

Zeile 31:

* Multiple DDS & PA modules attachable to one controller

* DDS & PA module for 1.8-50MHz with up to 15W

–

Zeile 21:

* ""ICSP"" for in circuit serial programming of the PIC processor

+ **== Ausstattung: ==**

* Configuration software for Windows

Zeile 31:

* Multiple DDS & PA modules attachable to one controller

* DDS & PA module for 1.8-50MHz with up to 15W

+

*** BAnds (80m / 40m / 30m / 20m/ 17m / 15m / 12m / 10m / 6m)**

Version vom 1. Juli 2009, 09:30 Uhr

VERSATILE WSPR BEACON for MOBILE and FIXED applications

MEPT = Manned Experimental Propagation Transmitter



Es dauerte einige Monate - aber jetzt ist es (fast) fertig.

A versatile beacon concept that consists of a number modules that can be combined according to the application.

Anschlüsse:

- **USB interface** für die Windows Konfigurations Software
- **serial interface** zum Anschluss der GPS Maus
- **SPI bus** to interconnect the modules
- **ICSP** for in circuit serial programming of the PIC processor

Ausstattung\:

- Configuration software for Windows
- Beacon runs independent from PC
- Time and Location can be derived from GPS signal

-
- Autonomous generation of WSPR data string in local microcontroller
 - Up to 8 different filters selectable through filter switch box
 - Up to 4 Attenuator networks selectable through attenuator switch box
 - Multiple DDS & PA modules attachable to one controller
 - DDS & PA module for 1.8-50MHz with up to 15W
 - BAnds (80m / 40m / 30m / 20m/ 17m / 15m / 12m / 10m / 6m)

At the moment there are two modules. The CPU box with a DDS/PA module and a switch box that can hold up to 8 filter and one attenuator modules



Here you can find an overview of the possible configurations

MEPT CONFIGURATIONS

A detailed description of the individual modules can be found here

MEPT CPU

MEPT switch module

I have a long list of improvements and additions I want to create to my beacon system. Here is a list of my plans (Although I don't know yet where to find the time to do all that)

MEPT_Development_Plan

Weiter Informationen: <http://www.oel1fm.at/>