

TCE Tinycore Linux Project englisch

[Versionsgeschichte interaktiv durchsuchen](#)

[Visuell Wikitext](#)

Version vom 11. Juli 2012, 11:12 Uhr (Quelle anzeigen)

[OE2WAO](#) ([Diskussion](#) | [Beiträge](#))

[← Zum vorherigen Versionsunterschied](#)

Version vom 11. Juli 2012, 11:38 Uhr (Quelle anzeigen)

[OE2WAO](#) ([Diskussion](#) | [Beiträge](#))

[Zum nächsten Versionsunterschied →](#)

Zeile 1:

– **==Einleitung==**

[[Bild:PPC.jpg|thumb|500MHz LowPower industrial PC]]

This hamradio software project is based on [http://www.tinycorelinux.com TCE - Tinycore Linux], an embedded software system used on platforms like industrial pc, ALIX and others, and offers services and possibilities like

Zeile 11:

More information on the hamradio TCE - tinycore linux project coming here soon

Zeile 1:

+ **==Intro==**

[[Bild:PPC.jpg|thumb|500MHz LowPower industrial PC]]

This hamradio software project is based on [http://www.tinycorelinux.com TCE - Tinycore Linux], an embedded software system used on platforms like industrial pc, ALIX and others, and offers services and possibilities like

Zeile 11:

More information on the hamradio TCE - tinycore linux project coming here soon

+

+

+ **==Hardware==**

+ [[Bild:12v-anschluss.jpg|thumb|polarity industrial PC]]

+ **DH2IW Wolfgang, OE2WAO Mike and OE5DXL Chris are doing first experiments with discarded industrial pc hardware, a 500MHz AMD Geode CPU with up to 256MB of RAM, and a minimal power input of <5Watt (for remaining stock ask [http://www.oe2wao.info OE2WAO]).
**

+ **The operating system is placed on a CF memory card (>32MB).
**

+

- + **A USB soundcard is used for AFSK mods. One special character of working devices is a 3rd connector beside microphone and line out, the line in. Because these device are real stereo and make it possible to operate two separate channels on one sound card.**
- + **====Connections and conversion of the used industrial pc====**
- + **[[Bild:12v-umbau.jpg|thumb|power supply conversion 12V]]**
- + **There are several connectors (COM, USB, network) on the frontside of our panels, as you can see. For correct polarity it is important to connent the + pole to the right pin of the 3pol power supply connector, the pin which is closer to the USB ports. The negative pole is the left pin.
**
- + **The normal board supply is 24V.
**
- + **That we can use it with our 12V power supply, we have to do a little modification. Just add a 270k Ohm resistor on the bottom side of the power supply as shown in the picture.**

Version vom 11. Juli 2012, 11:38 Uhr


Inhaltsverzeichnis

1 Intro	3
2 Hardware	3
2.1 Connections and conversion of the used industrial pc	3
3 Help	4

Intro

This hamradio software project is based on [TCE - Tinycore Linux](#), an embedded software system used on platforms like industrial pc, ALIX and others, and offers services and possibilities like

- packet radio,
- APRS,
- lightning log,
- small webserver,
- SVX-Link (Echolink)



500MHz LowPower industrial PC

especialy in networks like HAMNET and similar.

One goal is a minimum on material expenditure and also a minimal current consumption, followed by a maximum of features


More information on the hamradio TCE - tinycore linux project coming here soon

Hardware

DH2IW Wolfgang, OE2WAO Mike and OE5DXL Chris are doing first experiments with discarded industrial pc hardware, a 500MHz AMD Geode CPU with up to 256MB of RAM, and a minimal power input of <5Watt (for remaining stock ask [OE2WAO](#)).

The operating system is placed on a CF memory card (>32MB).

A USB soundcard is used for AFSK mods. One special character of working devices is a 3rd connector beside microphone and line out, the line in. Because these device are real stereo and make it possible to operate two separate channels on one sound card.




polarity industrial PC

Connections and conversion of the used industrial pc

There are several connectors (COM, USB, network) on the frontside of our panels, as you can see. For correct polarity it is important to connent the + pole to the right pin of the 3pol power supply connector, the pin which is closer to the USB ports. The negative pole is the left pin.

The normal board supply is 24V.

That we can use it with our 12V power supply, we have to do a little modification. Just add a 270k Ohm resistor on the bottom side of the power supply as shown in the picture.



power supply conversion 12V

Help

If you need help on configuring the software packages you can contact us on packet radio convers channel 44.